

Explosion protection

Marking	ATEX: II 2G Ex h IIC T4 Gb X IECEX: Ex IIC T4 Gb NEC 500: Class I, Division 2, Group B,C and D NEC 505: Class I, Zone 1, AEx d e ib px IIB resp. IIB+H2 T3 resp. T4 CEC Sec. 18: Ex d e ib px IIC T3 resp. T4 TR CU: II Gb T4 X
---------	--

Technical data

Technology	Automatic tilting measuring cell
Method	compliant with: ASTM D97, DIN EN ISO 3016, IP 15 correlates with: ASTM D5949 Automatic Tilt Method similar to ASTM D5950
Measuring range	-30 to 33 °C (-22 to 91.4 °F)
Repeatability	≤ DIN EN/ASTM
Reproducibility	≤ DIN EN/ASTM
Measuring cycle	discontinuous, cycle time 15 to 90 min depends on pour point temperature
Product streams	1 x sample, 1 x validation (additional hardware required)
– Electrical data	
Nominal voltage	230 V AC ± 10 %, 1 phase; 50 Hz; other ratings on request
Maximum power consumption	approx. 300 W
– Protection class	
IP 54 (comparable to Nema 13)	
– Ambient conditions	
Ambient temperature	operation 5 to 40 °C (41 to 104 °F) storage 0 to 60 °C (32 to 140 °F)
Ambient humidity	operation 5 to 80 % relative humidity, non-corrosive storage 5 to 85 % relative humidity, non-corrosive
Sample	
Quality	filtered 50 µm, free of suspended water (≤ 37 cSt at inlet temperature)
Consumption	approx. 20 to 40 l/h
Pressure at inlet	1 to 3 bar (14.5 to 43.5 psi)
Temperature at inlet	normal: 30 to 50 °C (86 to 133 °F) min. 20 K above pour point temperature
Utilities	
– Instrument air Consumption	
Purge	8 Nm ³ /h while purging (~12 min)
Operation	approx. 0.8 Nm ³ /h
Pressure at inlet	2 to 5 bar (29 to 72.5 psi)
Quality	humidity class 2 or better acc. to ISO 8573.1
– Coolant	
controlled and supplied by chiller	

Signal outputs and inputs	
Analog outputs	pour point temperature (others on request)
Digital outputs	Alarm, Ready/Valid
Digital inputs	Stream Selection, Validation Request, Reset
Electrical data of signal outputs and inputs	
Analog outputs	max. 8 (4 to 20 mA; 1000 Ω) active isolated on request
Analog inputs	4 to 20 mA; 160 Ω
Digital outputs	24 V DC; max. 0.5 A
Digital inputs	high: 15 to 28 V DC low: 0 to 4 V DC
Auxiliary power supply output	24 V DC; max. 0.8 A
Control unit	
Central control unit	Industrial PC
Operating system	Windows 10 Enterprise LTSC
Control software	PACS
User interfaces	
Display	TFT display with touch function 1366 x 768 pixel
Keyboard	virtual keyboard, controlled via TFT display with touch function
Connections	
Tube fittings	Swagelok® 6 mm/8 mm/12 mm/18 mm other fittings on request
Vent/Drain	open to atmosphere, backpressure on request
Weight and dimensions	
Weight	approx. 300 kg (without options)
Dimensions (W x H x D)	approx. 1140 x 1900 x 710 mm
Space requirements	right: 150 mm/left: 100 mm
Optional interfaces	
Analog outputs	on request
MODBUS interface	MODBUS/RTU via RS485 or RS422 or FOC is, MODBUS/TCP via FOC is
Remote access	via Ethernet (VDSL or FOC is)



Representantes / Distribuidores Exclusivos

 Argentina

Tel: (+54 11) 5352 2500

Email: info@dastecsrl.com.ar

Web: www.dastecsrl.com.ar

 Uruguay www.dastecsrl.com.uy

 Bolivia www.tecdas.com.bo